

# **ISONEM M 36**

Revision nr.2 **Revision Date:** 30/03/2018

Printed on: 30/03/2018

Page n. 1/8

# SAFETY DATA SHEET

According to Regulation (EC) No. 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code M 36

Product name **ISONEM M 36** 

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Cement based, rapid setting plug mortar for stopping the leakages

### 1.3. Details of the supplier of the safety data sheet

ISONEM BOYA VE YALITIM TEKNOLOJILERI INS. SAN. TIC. A.S.

Full address ITOB OSB 10001 SK. NO:20 TEKELI

District and Country 35470 Menderes / IZMIR

TURKEY

Tel. +90 232 799 04 95 Fax +90 232 437 01 33

e-mail address of competent person

isonem@isonem.com.tr responsible for safety data sheet

#### 1.4. Emergency telephone number

For urgent inquiries refer to +90 232 799 04 95

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is not classified as hazardous according to regulation (EC) 1272/2008 of the European parliament and of the council, on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC and amending Regulation (EC) No 1907/2006.

# 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments

Hazard classification and indication:

H318 Eve Dam. 1 Skin Irrit. 2 H315 STOT SE 3 H335 Skin Sens. 1 H317

## 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.







# **ISONEM M 36**

Revision nr.2 Revision Date: 30/03/2018

Printed on: 30/03/2018

Page n. 2/8

Signal words: Danger

H318 Causes serious eye damage.H315 Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

**P264** Wash . . . thoroughly after handling.

**P280** Wear protective gloves / protective clothing / eye protection / face protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P310 Immediately call a POISON CENTER or doctor / physician.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains: Portland cement

#### 2.3. Other hazards

Information not available.

# **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Information not relevant.

## 3.2. Mixtures

Contains:

Identification. Conc. %. Classification 1272/2008 (CLP).

Portland cement

CAS. 65997-15-1 20 - 40 Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1 H317

EC. - INDEX. -

# **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

Not specifically necessary. Observance of good industrial hygiene is recommended.

# 4.2. Most important symptoms and effects, both acute and delayed

No episodes of damage to health ascribable to the product have been reported.

# 4.3. Indication of any immediate medical attention and special treatment needed

Information not available.

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.



## **ISONEM M 36**

Revision nr.2 Revision Date: 30/03/2018

Printed on: 30/03/2018

Page n. 3/8

## UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

## 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

# 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## 6.3. Methods and material for containment and cleaning up

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

# 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s)

Information not available.

# **SECTION 8. Exposure controls/personal protection**

## 8.1. Control parameters

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.



# **ISONEM M 36**

Revision nr.2 **Revision Date:** 30/03/2018

Printed on: 30/03/2018

Page n. 4/8

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Powder

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance Colour Not available Odour Not available Odour threshold. Not available Not available рΗ Melting point / freezing point. Not available Initial boiling point. Not available Boiling range. Not available Flash point. Not applicable **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit. Not available Upper inflammability limit. Not available Lower explosive limit. Not available Upper explosive limit. Not available Vapour pressure. Not available Not available Vapour density Relative density. Not available Solubility Not available Partition coefficient: n-octanol/water Not available Auto-ignition temperature. Not available Not available Decomposition temperature. Viscosity Not available. Explosive properties Not available. Oxidising properties Not available



# **ISONEM M 36**

Revision nr.2 Revision Date: 30/03/2018

Printed on: 30/03/2018

Page n. 5/8

#### 9.2. Other information

VOC (Directive 1999/13/EC):

VOC (volatile carbon):

# **SECTION 10. Stability and reactivity**

# 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available.

### 10.6. Hazardous decomposition products

Information not available.

# **SECTION 11. Toxicological information**

### 11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory trait. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: vapour inhalation may irritate the lower and upper respiratory tract and cause cough and respiratory disorders. At higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

Portland cement LD50 (Oral). > 2000 mg/kg Rat LD50 (Dermal). > 2000 mg/kg Rabbit

# **SECTION 12. Ecological information**



# **ISONEM M 36**

Revision nr.2 Revision Date: 30/03/2018

Printed on: 30/03/2018

Page n. 6/8

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

#### 12.1. Toxicity

Information not available.

## 12.2. Persistence and degradability

Information not available.

#### 12.3. Bioaccumulative potential

Information not available.

#### 12.4. Mobility in soil

Information not available.

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available.

# **SECTION 13. Disposal considerations**

## 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Avoid littering. Do not contaminate soil, sewers and waterways.

# CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

# **SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.

None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006. None.



# **ISONEM M 36**

Revision nr.2 **Revision Date:** 30/03/2018

Printed on: 30/03/2018

Page n. 7/8

Substances in Candidate List (Art. 59

REACH).

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg.

649/2012:

Substances subject to the Rotterdam Convention:

Substances subject to the Stockholm Convention:

None.

#### Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Dam. 1 Serious eye damage, category 1 Skin irritation, category 2 Skin Irrit. 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1 Causes serious eye damage H318 H315 Causes skin irritation

May cause respiratory irritation. H335 May cause an allergic skin reaction. H317

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%



# **ISONEM M 36**

Revision nr.2 Revision Date: 30/03/2018

Printed on: 30/03/2018

Page n. 8/8

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

Annex II to Regulation (EC) No. No. 1907/2006 (REACH) Commission Regulation EU No. 830/2015 of 28 May 2015

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments Regulation (EC) 1907/2006 (REACH) of the European Parliament Regulation (EC) 1272/2008 (CLP) of the European Parliament Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament Regulation (EC) 453/2010 of the European Parliament

The Merck Index. - 10th Edition Handling Chemical Safety

Niosh - Registry of Toxic Effects of Chemical Substances

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

History

Date of issue: 30-03-2018 Previous date: 28-01-2016

Version: 2

# Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper use.